

Koldingweg 19-1  
9723 HL Groningen

Postbus 5236  
9700 GE Groningen

T (050) 820 00 00  
F (050) 820 00 08  
E callvoip@callvoip.nl  
W www.callvoiptelefonie.nl

## Schermprints: Callvoip Business VDSL instellen op v2860

Log in en ga naar WAN → General Setup.

Kies WAN 1 (= xDSL interface) en stel deze in zoals hieronder aangegeven:  
(NB: na het opslaan wijzigt de indicator ADSL in VDSL)

### WAN >> General Setup

#### WAN 1

Enable:	Yes
Display Name:	
Physical Mode:	ADSL
DSL Mode:	Auto
Physical Type:	Auto negotiation
DSL Modem Code:	Default
Line Speed(Kbps):	
DownLink	0
UpLink	0
VLAN Tag insertion (ADSL):	Disable (for channel 1)
Tag value:	0 (0~4095)
Priority:	0 (0~7)
VLAN Tag insertion (VDSL2):	Enable
Tag value:	6 (0~4095)
Priority:	0 (0~7)
Active Mode:	Always On Load Balance: <input checked="" type="checkbox"/>

**Note :** In DSL auto mode, the router will reboot automatically while switching between VDSL2 and ADSL lines.

Klik op [OK] om de instellingen op te slaan.

ING BANK 5041280  
IBAN NL66INGB0005041280  
BIC INGBNL2A  
KVK 02066541  
BTW NL1041.63.252.B01

Ga vervolgens naar menu WAN → Internet Access.

Selecteer bij [WAN 1] als Access Mode: PPPoE / PPPoA en klik op [Details Page].

#### Internet Access

Index	Display Name	Physical Mode	Access Mode		
WAN1		ADSL / VDSL	PPPoE / PPPoA	Details Page	IPv6
WAN2		Ethernet	None	Details Page	IPv6
WAN3		USB	None	Details Page	IPv6

**Note :** Only one WAN can support IPv6.

De detailpagina van WAN 1 komt naar voren.

Vul die in zoals hieronder aangegeven.

WAN >> Internet Access

WAN 1

PPPoE / PPPoA      MPoA / Static or Dynamic IP      IPv6

Enable    Disable

**Modem Settings (for ADSL only)**

Multi-PVC channel: Channel 1

VPI: 0

VCI: 35

Encapsulating Type: VC MUX

Protocol: PPPoA

Modulation: Multimode

**PPPoE Pass-through**

For Wired LAN

For Wireless LAN

**WAN Connection Detection**

Mode: ARP Detect

Ping IP: [ ]

TTL: [ ]

MTU: 1442 (Max: 1492)

**ISP Access Setup**

Username: callvoip

Password: [ ]

Separate Account for ADSL

PPP Authentication: PAP or CHAP

Idle Timeout: -1 second(s)

IP Address From ISP: WAN IP Alias

Fixed IP:  Yes    No (Dynamic IP)

Fixed IP Address: [ ]

Default MAC Address

Specify a MAC Address

MAC Address: 00 · 1D · AA : AC · 1A · 51

Index(1-15) in Schedule Setup:

=> [ ] , [ ] , [ ] , [ ]

OK      Cancel

Klik vervolgens op OK om de instellingen op te slaan.

Wacht nu ca 5 minuten en kijk of u internetverbinding heeft.

Zo niet, check de bekabeling en doe de draytek dan eens uit, wacht ca 10 sec en doe hem dan weer aan. Komt de verbinding niet op, neem dan contact op met Callvoip voor verdere assistentie.

CallvoipTelefonie  
Koldingweg 19-1  
9723 HL GRONINGEN

T: 050-820 00 00  
F: 050-820 00 08  
callvoip@callvoip.nl