

Tijdhof Consulting Technotes
*Configuratie van uw
Sipura SPA-2002 VoIP gateway voor
BudgetPhone*

Tijdhof Consulting - 10 februari 2006



Sylvislaan 2 9728 NS Groningen | Postbus 1040 9701 BA Groningen
Telefoon 050 526 49 33 | Fax 050 526 49 63 | info@tijdhof.nl | www.tijdhof.nl

Configuratie van uw Sipura SPA-2002 voor BudgetPhone

Hieronder vindt u de schermprints van de configuratie van de SPA-2002 VoIP gateway voor BudgetPhone.

N.B.: bij veld [Proxy] dient u in te vullen wat BudgetPhone [SIP Server] noemt; bij [Outgoing Proxy] dient u in te vullen wat BudgetPhone [Proxy] noemt.

SIPURA
technology, inc.

Sipura Phone Adapter Configur

Info | System | SIP | Provisioning | Regional | Line 1 | **Line 2** | User 1 | User 2 | [User Login](#) [bg](#)

Line Enable: yes

Streaming Audio Server (SAS)

SAS Enable: no SAS DLG Refresh Intvl: 30

SAS Inbound RTP Sink:

NAT Settings

NAT Mapping Enable: no NAT Keep Alive Enable: yes

NAT Keep Alive Msg: \$NOTIFY NAT Keep Alive Dest: \$PROXY

Network Settings

SIP TOS/DiffServ Value: 0x68 Network Jitter Level: high

RTP TOS/DiffServ Value: 0xb8

SIP Settings

SIP Port: 5061 SIP 100REL Enable: no

EXT SIP Port: Auth Resync-Reboot: yes

SIP Proxy-Require: SIP Remote-Party-ID: no

SIP Debug Option: none RTP Log Intvl: 0

Restrict Source IP: no Referor Bye Delay: 4

Refer Target Bye Delay: 0 Referee Bye Delay: 0

Refer-To Target Contact: yes

Call Feature Settings

Blind Attn-Xfer Enable: no MOH Server:

Xfer When Hangup Conf: yes Conference Bridge URL:

Conference Bridge Ports: 3

Proxy and Registration

Proxy: budgetphone.nl Use Outbound Proxy: yes

Outbound Proxy: sip.budgetphone.nl Use OB Proxy In Dialog: yes

Register: yes Make Call Without Reg: no

Register Expires: 3600 Ans Call Without Reg: no

Use DNS SRV: no DNS SRV Auto Prefix: no

Proxy Fallback Intvl: 3600

Subscriber Information

Display Name: User ID: 31xxxxx

Password: ***** Use Auth ID: yes





Auth ID:	31xxxxx	
Mini Certificate:		
SRTP Private Key:		
Supplementary Service Subscription		
Call Waiting Serv:	yes	<input checked="" type="checkbox"/>
Block ANC Serv:	yes	<input checked="" type="checkbox"/>
Cfwd All Serv:	yes	<input checked="" type="checkbox"/>
Cfwd No Ans Serv:	yes	<input checked="" type="checkbox"/>
Cfwd Last Serv:	yes	<input checked="" type="checkbox"/>
Accept Last Serv:	yes	<input checked="" type="checkbox"/>
CID Serv:	yes	<input checked="" type="checkbox"/>
Call Return Serv:	yes	<input checked="" type="checkbox"/>
Three Way Call Serv:	yes	<input checked="" type="checkbox"/>
Attn Transfer Serv:	yes	<input checked="" type="checkbox"/>
MWI Serv:	yes	<input checked="" type="checkbox"/>
Speed Dial Serv:	yes	<input checked="" type="checkbox"/>
Referral Serv:	yes	<input checked="" type="checkbox"/>
Block CID Serv:	yes	<input checked="" type="checkbox"/>
Dist Ring Serv:	yes	<input checked="" type="checkbox"/>
Cfwd Busy Serv:	yes	<input checked="" type="checkbox"/>
Cfwd Sel Serv:	yes	<input checked="" type="checkbox"/>
Block Last Serv:	yes	<input checked="" type="checkbox"/>
DND Serv:	yes	<input checked="" type="checkbox"/>
CWCID Serv:	yes	<input checked="" type="checkbox"/>
Call Back Serv:	yes	<input checked="" type="checkbox"/>
Three Way Conf Serv:	yes	<input checked="" type="checkbox"/>
Unattn Transfer Serv:	yes	<input checked="" type="checkbox"/>
VMWI Serv:	yes	<input checked="" type="checkbox"/>
Secure Call Serv:	yes	<input checked="" type="checkbox"/>
Feature Dial Serv:	yes	<input checked="" type="checkbox"/>
Audio Configuration		
Preferred Codec:	G711u	<input checked="" type="checkbox"/>
Use Pref Codec Only:	no	<input checked="" type="checkbox"/>
G729a Enable:	yes	<input checked="" type="checkbox"/>
G723 Enable:	yes	<input checked="" type="checkbox"/>
G726-16 Enable:	yes	<input checked="" type="checkbox"/>
G726-24 Enable:	yes	<input checked="" type="checkbox"/>
G726-32 Enable:	yes	<input checked="" type="checkbox"/>
G726-40 Enable:	yes	<input checked="" type="checkbox"/>
DTMF Process INFO:	yes	<input checked="" type="checkbox"/>
DTMF Process AVT:	yes	<input checked="" type="checkbox"/>
DTMF Tx Method:	Auto	<input checked="" type="checkbox"/>
Hook Flash Tx Method:	None	<input checked="" type="checkbox"/>
Silence Supp Enable:	no	<input checked="" type="checkbox"/>
Silence Threshold:	medium	<input checked="" type="checkbox"/>
Echo Canc Enable:	yes	<input checked="" type="checkbox"/>
Echo Canc Adapt Enable:	yes	<input checked="" type="checkbox"/>
Echo Supp Enable:	yes	<input checked="" type="checkbox"/>
FAX CED Detect Enable:	yes	<input checked="" type="checkbox"/>
FAX CNG Detect Enable:	yes	<input checked="" type="checkbox"/>
FAX Passthru Codec:	G711u	<input checked="" type="checkbox"/>
FAX Codec Symmetric:	yes	<input checked="" type="checkbox"/>
FAX Passthru Method:	NSE	<input checked="" type="checkbox"/>
FAX Process NSE:	yes	<input checked="" type="checkbox"/>
Release Unused Codec:	yes	<input checked="" type="checkbox"/>
Dial Plan		
Dial Plan:	(*xx 11x 0xxxxxxxx 00xxxxxxxx 31xxxxxxxx <:071>xxxxxx 09).	
Enable IP Dialing:	no	<input checked="" type="checkbox"/>
FXS Port Polarity Configuration		
Idle Polarity:	Forward	<input checked="" type="checkbox"/>
Caller Conn Polarity:	Forward	<input checked="" type="checkbox"/>
Callee Conn Polarity:	Forward	<input checked="" type="checkbox"/>
		<input type="button" value="Undo All Changes"/> <input type="button" value="Submit All Changes"/>
User Login basic advanced		

Tijdhof Consulting | kennis in praktijk
 Sylviuslaan 2
 9728 NS GRONINGEN

sales@tijdhof.nl

www.tijdhof.com
 www.callvoip.nl
 www.thuiswerkshop.nl